

Additel 901A

Low Pressure Test Pump



- Generate 6 psi (0.4 bar) vacuum to 6 psi (0.4 bar) pressure
- Portable, only 3.5 lb
- Great stability and high resolution
- Minimal maintenance
- Hand-tight quick connectors

Distributor Indonesia
PT TRIWI PUTRA JAYA
 Taman Surya 3.H7.N0.17 Jl. Daan Mogot
 Pegadungan – Kalideres, Jakarta 11830
 ☎ +62 21 541 7194 Fax. +62 21 451 4630
 📠 +62 818 920 386 - +62 822 9908 5294
 📧 info@trwi-online.com / sales@pttriwi.com
 🌐 www.trwi-online.com / www.pttriwi.com



OVERVIEW

The 901A Low Pressure Test Pump is a hand operated pressure pump designed to generate pressures from -6 psi (-0.4 bar) to 6 psi (0.4 bar). A high-quality screw press is designed for fine pressure adjustment, with an adjustment resolution up to 0.1 Pa (0.001 mbar). The 901A is a very stable low pressure calibrator. It makes use of an isothermal bellows chamber which is designed for reducing the possible effects of environmental temperature change. Most pumps make use of a check valve (non-returning valve) and are not well insulated which will cause large fluctuations in pressure with a change in ambient temperature or when the unit is touched. The 901A does not use a check valve and is remarkably stable. Two hand-tight connectors installed on the pump allow easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches. The 901A is an ideal comparison test pump for low pressure applications.

FEATURES


- **Portable:** Only 3.5 lb (1.6 kg)
- **Adjustment Resolution**
0.1Pa (0.001 mbar); Specially designed screw press for fine pressure adjustment.
- **Great Stability**
Isothermal chamber: the pressure chamber is insulated to reduce the influence from environmental temperature changes.
Specially designed bellows minimize leakage to guarantee excellent stability.
- **Durable and Minimal Maintenance**
Without non-returning valve that is usually used on troublesome hand pump.
- **Easy-to-use**
Pressure could be set and adjusted precisely and quickly through a simple turn of the handle.
- **Hand-tight Quick Connectors**
Allows easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches.

SPECIFICATIONS

- **Media:** Air.
- **Generated Pressure Range**
6 psi (0.4 bar) vacuum to 6 psi (0.4 bar) positive pressure.
- **Adjustment Resolution:** 0.1 Pa (0.001 mbar).
- **Material:**
Ram/adapters: SS
Body: SS, aluminum
Seals: Buna-N, PTFE, Copper Alloy
- **Connection**
Hand-tight connectors for both test gauge and reference gauge.
1/4NPT female, 1/2NPT female, 1/4BSP female, 1/2BSP female, or M20X1.5 female
- **Dimensions:** Height: 5.7" (145mm)
Base: 9.65" (245 mm) x 6.50" (165mm)
- **Weight:** 3.5 lb (1.6 kg).
- **Warranty:** 1 year.

ORDERING INFORMATION

Model Number



Optional Accessories

| Model number | Description |
|--------------|---|
| ADT901-X-kit | Test kit for ADT901A (barb fitting, connection hoses, and adapters). X=connection type e.g. N-1/4NPTM, N2-1/2NPTM, B-1/4BSPM, B2-1/2BSPM, M-M20X1.5M. |
| ADT102 | Adapters and fittings, 1/4NPT male to various male and female connection (25 pcs). |
| ADT103 | Adapters and fittings, 1/4NPT (1/2NPT, 1/4BSP, 1/2BSP, or M20X1.5) male to various female hand-tight quick connectors (10 pcs). |
| 9901-901 | Carrying Case for one ADT901A pump and two ADT681 gauges or ADT672 calibrators |
| ADT901A-MK | Maintenance kit for Additel 901A pump |
| 9240 | Differential pressure gauge holder |

Note: For oil free applications contact Additel.

Accessories included

- O-ring: 20 pcs
- Manual: 1 pc
- Carrying case (901A-X-SETmodels only)